




**Nominal cooling duty**  
**Nominal heating duty**  
**Main power supply**  
**Plug type**  
**Plug type (Gas detection)**  
**Noise level (max)**  
**Weight**  
**Dimensions (L x W x H)**  
**Control**  
**Average power consumption**  
**Water connection**  
**Nominal water flow**  
**Ambient Operating Temperature Range**  
**Heating (Air Temperature Operating Range)**  
**Heating (Water Temperature Range)**  
**Cooling (Leaving Water Temperature Range)**  
**Refrigerant Gas**  
**GWP**

65 kW  
76 kW  
415 V 3 ph N+E 50 Hz Run 40.2 A  
BS4343 16 A, BS4343 63 A 5 pin  
BS4343 16 A Run 2 A  
50 dBA / 82 LWA @ 10 metres  
1,740 kg  
3,090 x 1,330 x 2,775 mm  
Automatic programmer  
12.5 kW/h  
50 mm (2") bauer  
3.6 l/s  
-2°C to +35°C  
-20°C to +35°C  
30°C to 55°C  
-15°C to +15°C  
R290  
3

## **Suitable applications include:**

Food and beverage	Events
Construction	Pharmaceuticals
Healthcare	Sever rooms
Manufacturing	Many more

 Cooling and heating